

Colt DELUXE

SUPREME PERFORMANCE,
EXHILARATING STYLE
AND EXCELLENT VALUE

COLT DELUXE

The sleek, sporty Colt Deluxe Scooter delivers smooth performance and all-new advanced standard features including rugged suspension, high-visibility automatic brake lights, feather-touch disassembly, an LED kerb light and a wraparound delta tiller.




(Images are for illustration purposes only)

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

Colt Deluxe

Weight capacity:	28 Stone 8 lbs. (181 kg)
Maximum speed ¹ :	Up to 6.25 mph (10.5 km/h)
Ground clearance ² :	5.7 cm (2.25") at motor
Turning radius ² :	133.35 cm (52.5")
Overall length ² :	119.4 cm (47")
Overall width ² :	56 cm (22")
Tyre size:	Front: 25.4 cm (10") solid Rear: 25.4 cm (10") solid
Suspension:	Front and rear
Total weight without batteries ^{2,4} :	68 kg (150 lbs.)
Heaviest piece when disassembled:	Front section: 29.48 kg (65 lbs.)
Standard seating:	Type: High back fold-flat seat with headrest and seat belt Weight: 19 kg (42 lbs.) Material: Black Vinyl Dimensions: width - 44.45 cm (17.5") overall width depth - 43.18 cm (17") effective depth
Seat-to-deck range ² :	47 cm - 49.5 cm (18.5" - 19.5")
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements ³ :	Two 12-volt, deep cycle Size: 31-36 AH or 40-45 AH (optional) Weight ⁵ : 31-36 AH: 10 kg (22.5 lbs.) each 40-45 AH: 14.74 kg (32.5 lbs.) each
Battery charger:	5-amp, off-board

Colours:



Features

- Front and rear suspension
- High-visibility automatic rear brake lighting system
- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Long-lasting, high-intensity LED headlight, taillight and indicators
- Exclusive stylish, lightweight, non-marking, low-profile wheels
- Auto-connecting front-to-rear harness
- Delta tiller with wraparound handles
- New LED battery meter for increased accuracy and visibility in any setting
- Includes pinchless hinges & eight-position seat rotation
- Easy-grip tiller adjustment knob
- Easy access, tiller-mounted charger port for standard dual voltage off-board charger
- Rearview mirror standard

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Rear basket
- Safety flag
- Walker holder

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of + 10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Includes standard seat.

⁵ Battery weight may vary based on manufacturer.

⁶ Tested in accordance with ISO 7176-22, 2000 and ISO 7176-11, 1992 standards.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk